



ADHESIVE APPLICATIONS

Our quotations will include one of the following appropriate adhesive applications:

OPTION A: Loose-Lay

For **indoor** installations customer wishing a more “portable option” may elect to “loose lay” the surface for easy removal or periodic cleaning. Customers electing to eliminate the use of adhesive may experience some shifting in the surface as a result of no adhesion. Degree of shifting will depend on the floor surface underneath the tiles as well as the degree of activity. However, if there are interior “open” pocket sections, treat those as “perimeter-to-tile”. Such a layout will have to be closely monitored for loose tiles which may case a tripping hazard. This is not a highly recommended solution.


Best for:

- Smaller indoor areas with limited activity
- Covering indoor wall-to-wall areas where the walls create the retaining border to hold tiles together

OPTION B: Perimeter-to-Tile

Holds the tile system together by using adhesive on the outer 12" of perimeter tiles (see grey perimeter area below). No need to use tile-to-base adhesive. Good for smaller indoor areas, with moderate activity. Tiles can be separated by cutting the adhesive bond between tiles.

Best for: Indoor areas with moderate to heavy activity




OPTION C: Tile-to-Tile + Perimeter to Base

To ensure minimum shifting of the tile system, use the adhesive with:

- tile-to-tile application for the whole area.
- tiles-to-base for the outer 12" of the perimeter

It is mandatory for any outdoor application as required by the warranty.

Best for: Large outdoor areas with heavy activity



Note: On hot, sunny days the rubber tiles will expand. For options C and D (above), the adhesive will reduce or eliminate any tiles from separating

	Loose Lay	Perimeter-to-Tile	Tile-To-Tile + Perimeter-to-Base
Indoor	Light Activity		
Indoor		Moderate Activity	
Indoor			Heavy Activity
Outdoor*			All Activity

For outdoor applications, use recommended application to keep warranty in effect.



136 Walker Street, Atlanta GA 30313
404-521-9054 Order 800-477-6434 Fax: 404-2228366
www.phunzone.com info@phunzone.com